

Kühlung 

Toleranz e8

Beschichtung TAC- $\alpha$

HA ETC HPC  $\neq$  

**NEW** 



Werkstoff / Material	Festigkeit / strength (N/mm <sup>2</sup> )	Vc m/min	Ø 0,1 - 2		Ø 3 - 4		Ø 5		Ø 6		Ø 8		Ø 10		Ø 12		Ø 16		Ø 20			
			ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD	ae= 1xD	ae= 0,3xD
			ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD	ap= 1xD
			fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)	fz (mm/Z)
Stahl / Steel	< 850																					
Stahl / Steel	< 1100																					
Stahl / Steel	< 1400																					
Gehärteter Stahl / Hardness Steel	< 55HRC																					
Gehärteter Stahl / Hardness Steel	< 60HRC																					
Gehärteter Stahl / Hardness Steel	< 67HRC																					
Gehärteter Stahl / Hardness Steel	≤ 70HRC																					
INOX	< 700																					
INOX	< 850																					
Guss / Castings																						
Aluminium / Al		260			0,035	0,045	0,05	0,06	0,055	0,065	0,055	0,065	0,06	0,07	0,065	0,075	0,075	0,09	0,09	0,11		
Kupfer / Cooper																						
Kunststoffe / Plastics		270			0,02	0,03	0,03	0,04	0,035	0,045	0,035	0,045	0,04	0,05	0,045	0,055	0,055	0,07	0,07	0,09		
Inconel																						
Titan / Titanium																						
Grafit / Graphite GFK / CFK																						

Bitte beachten, hierbei handelt es sich lediglich um Richtwerte! / Caution, these are only guide values!